## FLOW vertical form, fill and seal machine







- · Continuous motion machine.
- · Speed up to 200 bags/minute
- · EHEDG; stainless steel; hygienic design
- · High IP rating; IP 67 throughout the machine with IP 69K servo motors
- · Modular construction
- · Lenze PLC and electrical components
- · Servo driven sealing system, film transport and roll unwinding












## vertical form, fill and seal machine

Machine is standard equipped with:	Options:	FLOW
<ul> <li>EHEDG; stainless steel; hygienic design</li> <li>Lenze PLC with 15,4" full color touchscreen</li> <li>Film transport by means of vacuum, servo driven, pull belts</li> <li>Film cut and splice table</li> <li>Automatic lateral film adjustment</li> </ul>	QC-Seal system (LDPE, PP + Laminated films) Air cooling on sealing system Euroloch or handgrip sealing system Block bottom/gusset mechanism Lateral film guiding system Vibration unit	. বেববববৰ
<ul> <li>Photocell for bag length detection with pre-printed film</li> <li>End of film detection</li> <li>Pneumatic opening and closing of the servo driven film pull belts</li> </ul>	Bag support system  Connection for gas flushing (MAP)  Perforation systems	<b>8</b>
<ul> <li>Ergonomic film support with motorized drive and pneumatically locked axle</li> <li>Low power and air consumption</li> </ul>	Printing and labeling systems Various weighing and dosing systems Customer specific options on request	<b>V</b>
	, , , , , , , , , , , , , , , , , , , ,	J



Cover plate over the entire machine

## **Technical specifications**

Bag width (pillow) 80 - 350 mm Max. bag length unlimited mm Max. production speed 200 bpm Film thickness 25 - 130 µ Core diameter 76 (3") mm Max. film width 800 mm Max. outer diameter film roll 600 mm Power during production ca. 1.800 Watt Voltage 400 Volt/50 Hz/16 A

**FLOW** 

All dimensions and specifications are indications based on standard set up. Final details depend on customer specifications

**FLOW** 2.340 mm 1.430 mm 2.140 mm









Steenoven 18 5626 DK Eindhoven (NL) +31 (0)40 2095 040 sales@gkspackaging.com